

SERIE LAMPADE LED PL



39.940010*
PL-C 2 Pin G24d






39.94001*
PL-C 2 Pin G24d



39.94012*
PL-C 2 Pin G23



39.9404*
PL-L 4 Pin 2G11



Codice	Potenza	Equivalenza Watt	Lumen Φ360°	Kelvin	Attacco	CRI	Fascio (FA)	Dimensioni	Classe Energetica
39.940010C30	9W	66W	900lm	3000K	PL-C 2 Pin G24d	80	185°	Ø28x162mm	F
39.940010F65	9W	66W	900lm	6500K		80	185°	Ø28x162mm	F
39.940011C	9,5W	75W	1055lm	3000K		80	330°	Ø38x112mm	E
39.940011F	9,5W	75W	1055lm	6500K		80	330°	Ø38x112mm	E
39.940014C	13,5W	100W	1521lm	3000K		80	330°	Ø45x136mm	E
39.940014N	13,5W	100W	1521lm	4000K		80	330°	Ø45x136mm	E
39.940122C30	7W	54W	700lm	3000K	PL-C 2 Pin G23	80	330°	32x19x165mm	F
39.940122N40	7W	54W	700lm	4000K		80	330°	32x19x165mm	F
39.940123C30	9W	63W	850lm	3000K		80	330°	32x19x232mm	F
39.940123N40	9W	63W	850lm	4000K		80	330°	32x19x232mm	F
39.940410C30	10W	69W	950lm	3000K	PL-L 4 Pin 2G11	80	185°	44x20x220mm	F
39.940410N	10W	69W	950lm	4000K		80	185°	44x20x220mm	F
39.940416C30	14W	96W	1450lm	3000K		80	185°	44x20x310mm	F
39.940416N40	14W	96W	1450lm	4000K		80	185°	44x20x310mm	F
39.940420C30	18W	120W	1900lm	3000K		80	185°	44x20x410mm	F
39.940420N40	18W	120W	1900lm	4000K		80	185°	44x20x410mm	F
39.940430C30	25W	162W	2600lm	3000K		80	185°	43,5x24x535mm	F
39.940430N40	25W	162W	2700lm	4000K		80	185°	43,5x24x535mm	F